


EXTERNAL FINISH


 PROFILED STEEL PANEL WALLS


 FLAT STEEL PANEL WALLS


WINDOWS


 WINDOW - ALUMINIUM - SINGLE 4mm CLEAR GLAZED - SLIDING - BOTH PANES TO SLIDE AND LOCK - SIZE AS REFERENCE


 WINDOW - ALUMINIUM - SINGLE 4mm CLEAR GLAZED - TOP OPENING VENT - SIZE AS REFERENCE


 WINDOW - ALUMINIUM - DOUBLE GLAZED 4mm CLEAR / 6mm / 4mm CLEAR - SLIDING - BOTH PANES TO SLIDE AND LOCK - SIZE AS REFERENCE


 WINDOW - ALUMINIUM - DOUBLE GLAZED 4mm CLEAR / 6mm / 4mm CLEAR - TOP OPENING VENT - SIZE AS REFERENCE


 WINDOW - PVCu - DOUBLE GLAZED 4mm CLEAR / 20mm / 4mm CLEAR - FULLY OPENING - LOCKABLE - SIZE AS REFERENCE

 WINDOW - PVCu - DOUBLE GLAZED 4mm CLEAR / 20mm / 4mm CLEAR - TILT/TURN - LOCKABLE - SIZE AS REFERENCE

 WINDOW - PVCu - DOUBLE GLAZED 4mm CLEAR / 20mm / 4mm CLEAR - SLIDING - ONE PANE TO SLIDE AND LOCK - SIZE AS REFERENCE

 WINDOW - PVCu - DOUBLE GLAZED 4mm CLEAR / 20mm / 4mm CLEAR - FIXED - SIZE AS REFERENCE

 WINDOW - HIGH LEVEL - ALUMINIUM - SINGLE 4mm OBSCURE GLAZED - SLIDING - ONE PANE FIXED AND ONE PANE TO SLIDE AND LOCK - SIZE AS REFERENCE

 WINDOW - HIGH LEVEL - PVCu - DOUBLE GLAZED 4mm OBSCURE / 20mm / 4mm CLEAR - FULLY OPENING - SIZE AS REFERENCE

TG TOUGHENED GLAZING

 WINDOW EXTERNAL SHUTTER - MILD STEEL

 WINDOW EXTERNAL MESH GUARD - POWDER COATED - WHITE

 ROLLER SHUTTER - POWDER COATED - TYPE & COLOUR AS REFERENCE

 WINDOW BLIND - VENETIAN


 WINDOW BLIND - VERTICAL


(ROLLER) WINDOW BLIND - ROLLER

((FC - RATING)) FIRE CURTAIN - FIRE RESISTANCE IN MINUTES AS REFERENCE

DOORS

 EXTERNAL PERSONNEL DOOR - MILD STEEL - NON INSULATED - SIZE & FURNITURE AS REFERENCE

 EXTERNAL PERSONNEL DOOR - MILD STEEL - INSULATED SPECIFICATION - 80mm 0.040 W/mK INSULATION - SIZE & FURNITURE AS REFERENCE

 INTERNAL PERSONNEL DOOR - BLONDE OAK - HOLLOW CORE UNLESS INDICATED - SIZE & FURNITURE AS REFERENCE

PVCu PVCu SPECIFICATION DOOR

ALUM ALUMINIUM SPECIFICATION DOOR

EG EXTERIOR GRADE SPECIFICATION - INTERNAL DOOR - STAIN FINISHED UNLESS INDICATED

SC SOLID CORE SPECIFICATION - INTERNAL DOOR

2XG GLAZED - TOP PANEL ONLY

2XGG GLAZED - TOP AND BOTTOM PANEL

VP - GWPP VISION PANEL - GEORGIAN WIRED POLISHED PLATE GLASS

VP - TG VISION PANEL - TOUGHENED GLASS

DL5 DEADLOCK - 5 LEVER

AP PADLOCK - ARMOURD

BB1 BARREL BOLT - STRIAIGHT

BB2 BARREL BOLT - SWAN NECK

SB1 SPRING BOLT - 16mm DIAMETER x 265mm

SB2 SPRING BOLT - 12mm DIAMETER x 160mm

SB3 SPRING BOLT - 10mm DIAMETER x 144mm

ML MORTICE LOCK

RML REBATED MORTICE LOCK

FE FIRE EXIT

EO EXTERNAL OVERRIDE - FITTED TO FIRE EXIT

FL/TL FACILITY LEVER & TUBULAR LATCH - FITTED TO DISABLED WC DOOR

BL BATHROOM LOCK

IB1 INDICATOR BOLT

IB2 INDICATOR BOLT C/W EXTERNAL RELEASE

IB3 INDICATOR BOLT - OUTWARD OPENING

DC1 DOOR CLOSER - EXTERNAL

DC2 DOOR CLOSER - INTERNAL

WTT WEATHER THRESHOLD TRIM

DGL1 DIGITAL CODE MORTICE LOCK - EXTERNAL

DGL2 DIGITAL CODE MORTICE LOCK - INTERNAL DOOR

DGL3 DIGITAL CODE MORTICE LOCK - INTERNAL HALF GLAZED DOOR

CH CABIN HOOK


((FC - RATING)) FIRE CURTAIN - FIRE RESISTANCE IN MINUTES AS REFERENCE

EXTERNAL FITTINGS

 PROTECTIVE SHROUD - FOR SERVICE CONNECTIONS

 PROTECTIVE SHROUD - REMOVABLE FOR SERVICE CONNECTIONS

 CLOSE COUPLED LINK FACILITY

 CABLE ENTRY TUBE - 25mm C/W EXTERNAL CAP (SHOWN WITHIN EXTERNAL WALL)

 LOUVRE VENT - EXTERNAL - SIZE AS REFERENCE

VENT H VENT - HIGH LEVEL

VENT L VENT - LOW LEVEL

VENT R VENT - ROOF LEVEL

LB L LADDER BRACKET

CG C CABLE GUIDES

 RWP RAIN WATER PIPE & GUTTERING

CS1 CLIENT STICKER

CS2 CLIENT SIGN

SP SIGN PLATE - ALUMINIUM - POSITION & SIZE AS PER STICKER DRAWING

GENERATORS

GVO GENERATOR VENT OUT

GVI GENERATOR VENT IN

GCP GENERATOR CONTROL PANEL

GFF GENERATOR FUEL FILLER

GE GENERATOR EXHAUST

GEM GENERATOR ENGINE MANAGEMENT

DRAWING LEGEND

Issue	Page
-------	------

3.9	1 OF 4
-----	--------

ELECTRICAL - LIGHTING

	WALL LIGHT SWITCH - 1 GANG/1 WAY
	WALL LIGHT SWITCH - 2 GANG/1 WAY
	WALL LIGHT SWITCH - 1 GANG/2 WAY
	DIMMER LIGHT SWITCH
	OVERRIDE SWITCH FOR MOTION SENSOR - OFF ONLY
	PULL LIGHT SWITCH
	OVERRIDE PULL SWITCH FOR MOTION SENSOR - OFF ONLY
	KEY SWITCH FOR EMERGENCY LIGHT
	ROCKER SWITCH FOR ELECTRIC ROLLER SHUTTER
	BULKHEAD LIGHT - EXTERNAL
	BULKHEAD LIGHT - EXTERNAL C/W P.I.R
	FLOOD LIGHT - EXTERNAL
	BULKHEAD LIGHT - SLIM-LINE - EXTERNAL DUSK TO DAWN / ENERGY SAVING
	BULKHEAD LIGHT - SLIM-LINE - EXTERNAL C/W P.I.R
	FLOOD LIGHT - EXTERNAL C/W P.I.R
	BULKHEAD LIGHT - EXTERNAL C/W P.I.R / HIGH FREQUENCY 3 HOUR EMERGENCY
	FLOOD LIGHT - EXTERNAL LED C/W DUSK TO DAWN / ENERGY SAVING
	BULKHEAD LIGHT - INTERNAL
	EMERGENCY LIGHT - 3 HOUR NON-MAINTAINED
	EMERGENCY LIGHT - 3 HOUR MAINTAINED
	BATTEN LIGHT - SINGLE T8 TUBE - SIZE AS REFERENCE
	BATTEN LIGHT - TWIN T8 TUBE - SIZE AS REFERENCE
	READING LIGHT C/W PULLSTRING
	120° WALL MOUNTED MOTION SENSOR
CAT2	CAT2 LIGHT FITTING - UPGRADE FROM STANDARD SPECIFICATION
HF	HIGH FREQUENCY LIGHT FITTING - UPGRADE FROM STANDARD SPECIFICATION
T5	T5 LIGHT FITTING - UPGRADE FROM STANDARD SPECIFICATION
LED	LED LIGHT FITTING - UPGRADE FROM STANDARD SPECIFICATION
VP	VAPOUR PROOF LIGHT FITTING - UPGRADE FROM STANDARD SPECIFICATION
DIM	DIMMABLE LIGHT FITTING - UPGRADE FROM STANDARD SPECIFICATION
DIFF	DIFFUSER
MESH	REINFORCED MESH SPECIFICATION LIGHT FITTING

ELECTRICAL - CIRCUIT PROTECTION & CONTROL

	MAINS BOARD - SINGLE PHASE
	MAINS BOARD - THREE PHASE
	7 DAY TIMER - FITTED IN MAINS BOARD
	EARTH BOLT
	ANGLED APPLIANCE INLET - SIZE AS REFERENCE
	STRAIGHT CONNECTOR TO SUIT INLET - SIZE AS REFERENCE SUPPLIED LOOSE
	EXTERNAL SOCKET OUTLET - SIZE AS REFERENCE
	EXTERNAL SOCKET OUTLET C/W SWITCH - SIZE AS REFERENCE
	EXTERNAL ROTARY SURFACE ISOLATOR - SIZE AS REFERENCE
	ELECTRICAL ENERGY MONITOR
	WEATHER RESISTANT IP55 JUNCTION BOX - SURFACE MOUNTED PLASTIC ENCLOSURE
	WEATHER RESISTANT IP56 JUNCTION BOX - SURFACE MOUNTED PLASTIC ENCLOSURE

ELECTRICAL - WIRING DEVICES

	DOUBLE SOCKET - HIGH LEVEL
	DOUBLE SOCKET - WITHIN TRUNKING
	DOUBLE SOCKET - LOW LEVEL
	SINGLE SOCKET - HIGH LEVEL
	SINGLE SOCKET - WITHIN TRUNKING
	SINGLE SOCKET - LOW LEVEL
	FUSED SPUR - SWITCHED
	FUSED SPUR - UNSWITCHED
	EARTH BOND - SPARE
	TELEPHONE POINT
	THERMOSTAT - STANDARD
	THERMOSTAT - TAMPER PROOF
	COOKER POINT
	SHAVER SOCKET
IP-RATED	WEATHER RESISTANT - RATING AS REFERENCE
FM	FLOOR MOUNTED
CM	CEILING MOUNTED

ELECTRICAL - HEATING & VENTILATION






	EXTRACTION FAN - WALL MOUNTED - SIZE AS REFERENCE
	EXTRACTION FAN C/W HUMIDISTAT - WALL MOUNTED - SIZE AS REFERENCE
	EXTRACTION FAN - CEILING MOUNTED - SIZE AS REFERENCE
	HAND DRYER 1.8KW - WARNER HOWARD
	HAND DRYER 2.4KW - NEWLEC
	HAND DRYER - MITSUBISHI JET
	HAND DRYER 2.5KW - WARNER HOWARD
	HAND DRYER - 1.1KW - WARNER HOWARD AIRFORCE
	AIR CONDITIONING - INTERNAL UNIT - COOLING CAPACITY AS REFERENCE/HEATING CAPACITY AS REFERENCE - MOUNTED ON INTERNAL WALL ABOVE WINDOW HEIGHT - 24 HOUR TIMER
	AIR CONDITIONING - INTERNAL UNIT - COOLING CAPACITY AS REFERENCE/HEATING CAPACITY AS REFERENCE - MOUNTED ON INTERNAL WALL ABOVE WINDOW HEIGHT - 24 HOUR / 7 DAY TIMER
	AIR CONDITIONING - EXTERNAL CONDENSER UNIT - MOUNTED ON CANTILEVER BRACKETS ON EXTERNAL WALL BELOW WINDOW HEIGHT - UNIT IS FITTED WITH AN EXTERNAL DRAINAGE PIPE DISCHARGING TO GROUND
	CONVECTOR HEATER C/W THERMOSTAT - SIZE AS REFERENCE
	CONVECTOR HEATER - CONSORT DEFLECTOR SPECIFICATION - SIZE AS REFERENCE
	PANEL HEATER C/W THERMOSTAT - SIZE AS REFERENCE
	FAN HEATER C/W THERMOSTAT - SIZE AS REFERENCE
	COLDWATCHER HEATER - SIZE AS REFERENCE
	TUBULAR HEATER & GUARD - SIZE AS REFERENCE
	OIL FILLED RADIATOR C/W THERMOSTAT - SIZE AS REFERENCE
	HEATING CONTROLLER - CONSORT SLPB C/W RUN BACK TIMER & FIXED THERMOSTAT. SYSTEM WILL BE SET AT INSTALLATION TO TIMER MODE WITH 30 MINUTE TIME SEGMENTS AND A STANDARD TEMPERATURE OF 21°C
	HEATING CONTROLLER - CONSORT SLVT C/W RUN BACK TIMER & SEMI-ADJUSTABLE THERMOSTAT. SYSTEM WILL BE SET AT INSTALLATION TO TIMER MODE WITH 30 MINUTE TIME SEGMENTS AND A STANDARD TEMPERATURE OF 21°C
	HEATING CONTROLLER - CONSORT SLTI PROGRAMMABLE 7 DAY TIMER & THERMOSTAT. SYSTEM HAS INTEGRATED BATTERY BACKUP TO RETAIN SETTINGS FOR UP TO 1 YEAR AFTER DISCONNECTION FROM POWER SUPPLY
	(T) 24 HOUR TIMER SPECIFICATION HEATER - OPERATION IS SUBJECT TO CONTINUITY OF THE ELECTRICAL POWER SUPPLY
MESH	MESH GUARD FITTED TO HEATER



























DRAWING LEGEND

Issue	Page
3.9	2 OF 4



















ELECTRICAL - COMMUNICATIONS & DATA CABLING

-  16 PORT SWITCH 10/100 MBPS C/W PATCH LEADS
-  RJ45 2-WAY DATA SOCKET - WIRED USING CAT 5E CABLE TO T568B
-  RJ45 4-WAY DATA SOCKET - WIRED USING CAT 5E CABLE TO T568B
-  VOICE CONVERTER - FITTED TO SINGLE RJ45 DATA SOCKET
-  HDMI SOCKET
- TYPE TRUNKING - TYPE AS REFERENCE
- NW WIRING NOT INCLUDED




ELECTRICAL - ALARMS + ACCESS CONTROL

-  ALARM - DISABLED WC - SOUNDER & LIGHT
-  ALARM - DISABLED WC - PULL CORD
-  ALARM - DISABLED WC - MASTER RESET
-  SMOKE ALARM - MAINS WITH BATTERY BACKUP - IONISATION
-  SMOKE ALARM - BATTERY
-  SMOKE DETECTOR & SOUNDER - FIRE ALARM
-  SMOKE DETECTOR - FIRE ALARM
-  HEAT DETECTOR - FIRE ALARM
-  HEAT DETECTOR C/W SOUNDER - FIRE ALARM
-  HEAT ALARM - MAINS WITH BATTERY BACKUP
-  INTERNAL SOUNDER
-  MANUAL CALL POINT
-  PASSIVE INFRA RED DETECTOR
-  EXTERNAL BELLBOX & STROBE
-  DOOR CONTACT
-  TELEPHONE TO RELEASE BUTTON
-  PUSH TO RELEASE BUTTON
-  MAGNETIC DOOR RELEASE
-  FIRE ALARM MAIN PANEL
-  INTRUDER ALARM MAIN PANEL
-  INTRUDER ALARM REMOTE KEYPAD
-  ACCESS CONTROL MAIN PANEL
-  ACCESS CONTROL KEYPAD WITH CAMERA
-  ALARM - EXTERNAL SOUNDER











ELECTRICAL - WATER HEATING

-  WATER HEATER - STORAGE 2KW OVERSINK 5L
-  WATER HEATER - INSTANTANEOUS 3KW OVERSINK - TOUCH FREE
-  WATER HEATER - STORAGE 2KW UNDERSINK 10L
-  WATER HEATER - STORAGE 3KW 25L GRAVITY FED - POSITIONED AT HIGH LEVEL
-  WATER HEATER - STORAGE 3KW 10L - POSITIONED AT HIGH LEVEL
-  WATER HEATER - STORAGE 2KW UNDERSINK 15L
-  WATER HEATER - STORAGE 3KW UNDERSINK 15L
-  WATER HEATER - STORAGE 2KW UNDERSINK 5L
-  WATER HEATER - STORAGE 3KW UNDERSINK 10L
-  WATER HEATER - STORAGE 3KW 30L - POSITIONED AT HIGH LEVEL
-  WATER HEATER - STORAGE 3KW 50L - POSITIONED AT HIGH LEVEL
-  WATER HEATER - STORAGE 3KW 100L - POSITIONED AT HIGH LEVEL
-  INSTANT BOILING WATER SYSTEM - 3 LITRE, 18 CUP
-  INSTANT BOILING WATER SYSTEM - 5 LITRE, 30 CUP
-  INSTANT BOILING WATER SYSTEM - 7.5 LITRE, 45 CUP
-  INLINE FILTER FITTED TO INSTANT BOILING WATER SYSTEM
-  DRIP TRAY FOR INSTANT BOILING WATER SYSTEM
-  ELECTRIC SHOWER HEATER - SIZE AS REFERENCE



FLOOR

-  CARPET TILES
-  ALUMINIUM TREADPLATE FLOORING
-  MATWELL - COCONUT

FURNITURE & INTERNAL FITTINGS - FITTINGS

- NB1 NOTICE BOARD - 1200mm (W) X 1200mm (H) - SUNDEALA 9mm - PLASTIC TRIM
- NB2 NOTICE BOARD - 2400mm (W) X 1200mm (H) - SUNDEALA 9mm - PLASTIC TRIM
- NB3 NOTICE BOARD - 1800mm (W) X 1200mm (H) - SUNDEALA 9mm - PLASTIC TRIM
- NB4 BLUE BOARD - 1800mm (W) X 1200mm (H) - BLUE FELT - ALUMINIUM TRIM
- NB5 NOTICE BOARD - 1635mm (W) X 1200mm (H) - SUNDEALA 9mm - PLASTIC TRIM
- NB6 NOTICE BOARD - 2035mm (W) X 1200mm (H) - SUNDEALA 9mm - PLASTIC TRIM
- WB1 WHITE BOARD - 1200mm (W) X 900mm (H)
- WB2 WHITE BOARD - 1800mm (W) X 900mm (H)
- WT WORKTOP
- FB FIRE BLANKET
-  HAT & COAT HOOKS - QUANTITY AS SHOWN
-  TOILET ROLL HOLDER - SUPPLIED WITHOUT TOILET ROLL
-  MIRROR - 300mm (W) X 450mm (H)
-  DUCK BOARD - 500mm (W) X 383mm (L)
-  PAPER TOWEL DISPENSER - SUPPLIED WITHOUT PAPER TOWELS
-  DEB 1 DEB NATURALLY SKIN SAFETY CENTRE - 800mm (W) X 570mm (H) - 1 X PROTECT (1000ml), 1 X CLEANSE LIGHT (2000ml), 1 X CLEANSE HEAVY (4000ML), 1 X RESTORE (1000ml)
-  DEB 2 DEB NATURALLY MINI SKIN SAFETY CENTRE - 590mm (W) X 510mm (H) - 1 X PROTECT (1000ml), 1 X CLEANSE (2000ml), 1 X RESTORE (1000ml)
-  DEB 3 DEB CRADLE SKIN SAFETY CENTRE - 350mm (W) X 335mm (H) - 1 X PROTECT (700ml), 1 X CLEANSE (750ml), 1 X SANITISER (700ml)
-  VANITY PANEL
- SSB SPLASHBACK - STAINLESS STEEL
- PSB SPLASHBACK - PVCu
-  SOAP DISPENSER - SUPPLIED WITHOUT SOAP

FURNITURE & INTERNAL FITTINGS - LOCKERS


-  SOLID LOCKER - NUMBER OF COMPARTMENTS AS REFERENCE - 300mm (D) x 300mm (W) x 1800mm (H) - NO FEET - POWDER COATED FINISH IN LIGHT GREY UNLESS OTHERWISE SPECIFIED
-  MESH LOCKER - NUMBER OF COMPARTMENTS AS REFERENCE - 300mm (D) x 300mm (W) x 1980mm (H) - INCLUDING 150mm FEET - GALVANISED FINISH
- L1 DEAD LOCK C/W 2 KEYS
- L2 HASP & STAPLE - NO PADLOCK
- L3 HASP & STAPLE - C/W PADLOCK


DRAWING LEGEND

Issue	Page
3.9	3 OF 4



FURNITURE & INTERNAL FITTINGS - TABLES & SEATING

 TABLE & SLATTED BENCH SEATING -
SIZE AS REFERENCE

 TABLE & POLYPROPYLENE SEATING -
SEAT COLOUR AS REFERENCE
SIZE AS REFERENCE


 BENCH SEATING - SLATTED TIMBER
- STAINED FINISH

 CHAIR - POLYPROPYLENE STACKING

 CHAIR - HIGH BACK OFFICE

 CHAIR - UPHOLSTERED STACKING



FURNITURE & INTERNAL FITTINGS - STORAGE

 BASE UNIT - WHITE UNLESS SPECIFIED - SIZE
AS REFERENCE












 WALL UNIT - WHITE UNLESS SPECIFIED - SIZE
AS REFERENCE

 STEEL RACKING - TIER AS REFERENCE


PLUMBING - SERVICES

-  WATER METER
-  AIR ADMITTANCE VALVE
- CW** COLD WATER FEED CONNECTION FOR DISHWASHER,
WASHING MACHINE OR SIMILAR
- WO** WASTE OUTLET FOR DISHWASHER,
WASHING MACHINE OR SIMILAR
- 15mm** 15mm MAINS WATER INLET
- 22mm** 22mm MAINS WATER INLET
- 40mm** 40mm WASTE OUTLET
- 110mm** 110mm WASTE OUTLET

PLUMBING - BASINS & SINKS




-  WASH HAND BASIN - VITREOUS CHINA -
HSE COMPLIANT SIZE - COLD BASIN PILLAR TAP ONLY
-  WASH HAND BASIN - VITREOUS CHINA -
HSE COMPLIANT SIZE - HOT & COLD BASIN PILLAR TAPS
-  WASH HAND BASIN - VITREOUS CHINA -
COMPACT SIZE - COLD BASIN PILLAR TAP ONLY
-  WASH HAND BASIN - VITREOUS CHINA -
COMPACT SIZE - HOT & COLD BASIN PILLAR TAPS
-  WASH HAND BASIN - POLYETHYLENE - GREY - HSE
COMPLIANT SIZE & COLD TAP ONLY - WATER TANK
CAPACITY 60 LITRES - REQUIRING INTERNAL FILLING UNLESS
OTHERWISE SPECIFIED - WASTE DISCHARGES INTO
COMPANION WC TANK WHERE FITTED
-  SINK - VITREOUS CHINA - BELFAST SIZE - COLD BIB TAP ONLY
-  SINK - VITREOUS CHINA - BELFAST SIZE - HOT & COLD BIB TAPS
-  SINK - STAINLESS STEEL - COLD HIGH NECK PILLAR TAP ONLY
-  SINK - STAINLESS STEEL - HOT & COLD HIGH NECK PILLAR TAPS
-  SINK - STAINLESS STEEL - INSET - COLD HIGH NECK PILLAR TAP ONLY
-  SINK - STAINLESS STEEL - INSET - HOT & COLD HIGH NECK PILLAR TAPS

 WASH TROUGH - STAINLESS STEEL - SIZE AS REFERENCE -
COLD BASIN PILLAR TAP ONLY









 WASH TROUGH - STAINLESS STEEL - SIZE AS REFERENCE -
HOT & COLD BASIN PILLAR TAPS

- NC1** TAP - NON-CONCUSSIVE - COLD TAP ONLY
- NC2** TAP - NON-CONCUSSIVE - HOT & COLD TAP
- BT1** TAP - BIB, EXTERNAL
- BT2** TAP - BIB, INTERNAL
- LT** TAP - LEVER
- MT** TAP - MIXER





PLUMBING - SHOWERS

-  SHOWER TRAY - CREAM - 745mm (W) x 684mm (L)
+ WALL LINER - CREAM C/W CURTAIN - WHITE
-  SHOWER TRAY - WHITE - SIZE AS REFERENCE + CUBICLE
ENCLOSURE C/W DOOR - DOOR TYPE AS REFERENCE
-  SHOWER TRAY - WHITE - 1200mm (W) X 750mm (L) - LOW
LEVEL DISABLED C/W WALL LINER - WHITE - FOLDING DOORS
+ FOLDING SEAT + CURTAIN - WHITE



PLUMBING - TOILETS & URINALS

-  WC PAN - VITREOUS CHINA - WHITE C/W TOILET SEAT
CISTERN - DUAL FLUSH - PART FLUSH IS 4 LITRES /
FULL FLUSH IS 6 LITRES
-  WC PAN - VITREOUS CHINA - WHITE - DISABLED LOW
LEVEL, CISTERN 6 LITRES, TOILET SEAT & GRAB RAILS
-  GRAB RAIL - DISABLED
- MAC** MACERATOR FITTED TO WC
-  WC - POLYETHYLENE - GREY - RE-CIRCULATING TANK,
CAPACITY 225 LITRES - REQUIRES INTERNAL EMPTYING
-  URINAL - VITREOUS CHINA
-  URINAL - VITREOUS CHINA - TIMED FLOW VALVE
-  URINAL - VITREOUS CHINA - WATERLESS
-  URINAL TROUGH - STAINLESS STEEL - SIZE AS REFERENCE
- C1** CISTERN 9 LITRES - URINAL
- C2** CISTERN 13.5 LITRES - URINAL

PLUMBING - PUMPS, DRAINS, VALVES & ANCILLARIES

-  WATER SOFTENER
-  WATER PUMP
-  WATER PUMP C/W ENCLOSURE -
ALUMINIUM - POWDER COATED - WHITE
-  FLOOR DRAIN
- PRV** PRESSURE REDUCING VALVE

PLUMBING - TANKS

-  WATER TANK, REQUIRING INTERNAL FILLING
UNLESS NOTED, CAPACITY AS REFERENCE, NO ENCLOSURE
-  WASTE TANK, REQUIRING INTERNAL EMPTYING
CAPACITY AS REFERENCE, NO ENCLOSURE

DRAWING LEGEND

Issue	Page
3.9	4 OF 4